

FOR THOSE WHO DEMAND MORE. **FARMALL A SERIES**

CASE IH
AGRICULTURE



MODELS	FARMALL 65A	FARMALL 75A	FARMALL 85A	FARMALL 95A	FARMALL 105A	FARMALL 115A
ENGINE						
No. of cylinders / capacity [cm ³] / type	3 / 2,930	3 / 2,930	4 / 3,200	4 / 4,500	4 / 4,500	4 / 4,500
Rated engine power ECE R120 ¹⁾ @ engine rpm [kW/hp(CV)/rpm]	48 / 65 @ 2,300	53 / 72 @ 2,300	60 / 82 @ 2,500	70 / 95 @ 2,500	78 / 106 @ 2,300	83 / 113 @ 2,300
Max torque ECE R120 ¹⁾ @ engine rpm [Nm@rpm]	261 @ 1,400	292 @ 1,400	328 @ 1,250	390 @ 1,300	425 @ 1,300	450 @ 1,300
Torque rise acc. OECD [%]	31.6	30.3	41	44	30.7	28.9
Fuel tank capacity [litres]	110	110	110	110	110	110
TRANSMISSION*						
Standard	12 Fwd / 12 Rev with mechanical shuttle			12 Fwd / 12 Rev with hydraulic Powershuttle		
Optional	12 Fwd / 4 Rev with mechanical shuttle		12 Fwd / 12 Rev with Powershuttle		-	-
Optional with creeper	20 Fwd / 12 Rev with mechanical shuttle			-	-	
DRIVE AND STEERING						
Front axle standard / optional	4WD / 4WD with limited slip differential					
POWER TAKE OFF						
Type	Mechanical		Mechanical Std / Servo PTO opt		Servo PTO (std)	
Rear pto speeds standard [rpm]	540 or 540 / 540E / proportional ground speed (depending on version)					
Rear pto speeds optional [rpm]	540 / 1000 / proportional ground speed					
HYDRAULIC SYSTEM						
Max pump flow – steering / rear hitch and external services	29 / 36		29 / 50		29 / 50	
Rear remote valves	2 mechanical standard / 3rd valve as option					
Rear linkage control type	MHC (Mechanical Hitch Control)					
Rear lift capacity [kg]	3,000		3,565		3,565	
WEIGHTS* AND DIMENSIONS²⁾						
Minimum weight [kg]	3,440		3,620		3,780	
Max Permissible total weight [kg]	5,400		5,800		6,500	
Max length [mm]	4115		4212		4322	
Min- max track width [mm]	1425 - 1925		1526 - 2024		1626 - 2024	
Max height over cab [mm]	2552		2583		2600	
Wheelbase - 4WD [mm]	2224		2422		2422	
STANDARD TYRES*						
Front 4WD	11.2R24	11.2R24	12.4R24	13.6R24	14.9R24	14.9R24
Rear	16.9R30	16.9R30	18.4R30	16.9R34	18.4R34	18.4R34

*) to comply with legislation and specification in your country

1) ECE R120 correspond to ISO TR14396 2) with standard tyres

LRZ LOADERS	LRZ 95	LRZ 100
Max. lift capacity [kg]	2,060	2,540
Max. height [mm]	3740	3740
Power range [hp]	70-100	70-110

Case IH recommends **AKCELA**™ lubricants



Safety never hurts! Always read the Operator's Manual before working with any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided.

This literature has been published for worldwide circulation. The standard and optional equipment and the availability of individual models may vary from one country to the next. Case IH reserves the right to undertake modifications without prior notice to the design and technical equipment at all times without this resulting in any obligation whatsoever to make such modifications to units already sold. Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of going to press, these are also subject to change without prior notice. Illustrations may show optional equipment or may not show all standard equipment.

CNH UK Ltd., Cranes Farm Road, Basildon, Essex SS14 3AD - © 2012 CASE IH - www.caseih.com - Farmall A Series-UK-BR - Free phone 00800 22 73 44 00 - Printed in Italy - 04/12 - TP01 - Cod. 12C0003/INB



Experience true magnitude.

You will enjoy the all new Farmall A cab, with improved ergonomics, less noise and a high visibility roof for front loader work.

